




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>5</sup> :  A61F 2/24	A1	(11) International Publication Number: WO 93/18721  (43) International Publication Date: 30 September 1993 (30.09.93)
<p>(21) International Application Number: PCT/GB93/00568</p> <p>(22) International Filing Date: 19 March 1993 (19.03.93)</p> <p>(30) Priority data: 9206449.2 25 March 1992 (25.03.92) GB</p> <p>(71) Applicant (for all designated States except US): THE UNIVERSITY OF LEEDS [GB/GB]; Leeds LS2 9JT (GB).</p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): FISHER, John [GB/GB]; 2 Thornlea Court, West Park Drive, Leeds LS16 5LY (GB).</p> <p>(74) Agent: GILL JENNINGS &amp; EVERY; Broadgate House, 7 Eldon Street, London EC2M 7LH (GB).</p>		<p>(81) Designated States: JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).</p> <p>Published With international search report.</p>

(54) Title: ARTIFICIAL HEART VALVE



## (57) Abstract

A flexible leaflet heart valve (1) to replace natural aortic or pulmonary valves of the heart, includes a frame (3) and flexible leaflets (2) attached to the frame (3). Each flexible leaflet (2) forms part of a surface of revolution having its axis of revolution substantially orthogonal to the direction of blood flow through the valve (1). The valve (1) has improved opening characteristics under low flow conditions, and allows a large range of leaflet geometries for the same size valve.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TC	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

ARTIFICIAL HEART VALVEBACKGROUND OF THE INVENTION

5 The present invention relates to artificial heart valves, and more particularly to flexible leaflet heart valves which are used to replace the natural aortic or pulmonary valves of the heart.

Conventionally, ball or disk valves are used to replace natural mitral or tricuspid aortic or pulmonary  
10 valves of the heart. These artificial valves comprise a rigid frame defining an aperture and a cage enclosing a ball or a disk. When blood flows in the desired direction, the ball or disk lifts away from the frame allowing the blood to flow through the aperture. The ball or disk is  
15 restrained by the cage by struts or by a pivot. When blood tries to flow in the reverse direction, the ball or disk becomes seated over the aperture and prevents the flow of blood through the valve. The disadvantage of these valves is that the ball or disk remains in the blood stream when  
20 the blood flows in the desired direction, and this causes a disturbance to blood flow.

More recently, flexible leaflet valves have been proposed which mirror natural heart valves more closely. These valves have a generally rigid frame and flexible  
25 leaflets attached to this frame. The leaflets are arranged so that, in the closed position, each leaflet contacts its neighbour thereby closing the valve and preventing the flow of blood. In the open position, the leaflets separate from each other, and radially open out towards  
30 the inner walls of an artery in which the valve is located. The leaflets are either made from chemically treated animal tissue or polyurethane material. The leaflets must be capable of withstanding a high back pressure across the valve when they are in the closed position, yet must be  
35 capable of opening with the minimum pressure across the valve in the forward direction. This is necessary to

ensure that the valve continues to correctly operate even when the blood flow is low, and to ensure that the valve opens quickly when blood flows in the desired direction.

5 A wide range of geometries are used to describe natural aortic valve leaflets during diastole, but these geometries cannot be used for valves made from pericardial or synthetic materials due to the approximately isotropic properties of such materials compared to the highly anisotropic material of the natural valve. Consequently, 10 different geometries have to be used to form flexible leaflet heart valves made from pericardial or synthetic materials with isotropic mechanical properties.

Conventional flexible leaflet heart valves have three substantially identical leaflets mounted onto the frame. 15 The leaflets have a range of designs, both in the geometry of the leaflet and the variations in thickness of the leaflets. Original flexible leaflet heart valves incorporate leaflets which are spherical or conical when in the relaxed state, that is when no pressure is acting on 20 the leaflet. More recently, cylindrical and ellipsoidal leaflets have been proposed. These leaflet geometries are formed with an axis of revolution in a plane generally parallel to the blood flow through the valve.

#### 25 DISCLOSURE OF THE INVENTION

According to the present invention, a flexible leaflet heart valve for controlling the flow of blood comprises a substantially rigid frame and a plurality of substantially identical flexible leaflets mounted on the frame, 30 characterised in that each flexible leaflet forms part of a surface of revolution having its axis of revolution lying in a plane substantially orthogonal to the direction of blood flow through the valve, and a shape defined by the equation:

35

$$z^2 + y^2 = 2R_1 (x - g) - \alpha (x - g)^2$$

where:  $g$  is the offset of the leaflet from the axis of the frame;  
 $R_L$  is the radius of curvature of the leaflet at  $(g, 0, 0)$ ; and  
5  $\alpha$  is the shape parameter and is greater than 0 and less than 1.

A flexible leaflet valve according to the present invention has improved opening characteristics under low  
10 flow conditions. The shape of the leaflets is such that the radius of curvature of the leaflet continuously increases in two directions away from the centre point of the free edge. By varying the radius of curvature, the leaflet shape may be varied and still fit within the frame.

15 The value of  $\alpha$  may be in the range of 0.2 to 0.8, but is preferably in the range 0.4 to 0.6, and more preferably is about 0.5.

Preferably,  $x$  is in the range of 0 to  $R_L$ ,  $y$  is in the range between  $-R_L$  and  $+R_L$ , and  $z$  lies in the range  
20  $-1.8 R_L$  to  $+0.2 R_L$ .

The valve preferably includes three leaflets, and in this case the valve closure is preferably effected by the surface adjacent the free edge of each leaflet making sealing contact with the two neighbouring leaflets. The  
25 frame on which the leaflets are mounted is preferably circular in cross-section, and has a size dependent upon the size of the aorta or pulmonary artery in which the valve is to be used.

Preferably, each leaflet is made from a polyurethane  
30 material, and has a variable thickness, preferably between 0.15 mm and 0.25 mm.

#### BRIEF DESCRIPTION OF THE DRAWINGS

An example of a flexible leaflet heart valve according  
35 to the present invention will be described with reference to the accompanying drawings, in which:-

Figure 1 shows an overall view of the valve;

Figure 2 shows a plan of the valve; and,

Figure 3 shows a cross section of one leaflet of the valve taken along the line A - A shown in Figure 2.

#### 5 DESCRIPTION OF PREFERRED EMBODIMENT

As shown in Figure 1, a flexible leaflet heart valve 1 includes three flexible leaflets 2 which are substantially identical to each other. The leaflets 2 have a free edge 4. The leaflets 2 are mounted symmetrically on  
 10 a frame 3. The valve 1 is positioned in an artery with the axis of the frame 3 generally co-axial to the axis of the artery, and hence in the same direction as the blood flow along the artery. The leaflets 2 form part of a paraboloid having its axis of revolution lying in a plane orthogonal  
 15 to the direction of blood flow.

Using cartesian geometry with the z direction being the direction of blood flow, the y direction orthogonal to this and extending from the centre of the free edge 4 of the leaflet 2, and the x direction being orthogonal to  
 20 both the y and z directions, then the shape of the leaflet is represented by the equation:

$$z^2 + y^2 = 2R_L (x - g) - \alpha (x - g)^2$$

25 where: g is the offset of the leaflet from the axis of the frame as shown in Figure 3;  
 $R_L$  is the radius of curvature of the leaflet at (g, 0, 0) as shown in Figure 2; and  
 $\alpha$  is the shape parameter, and is greater than 0  
 30 and less than 1.

If  $\alpha = 1$  the geometry of the leaflet 2 will be spherical. When  $\alpha = 0$ , the surface will be parabolic. However, for  $0 < \alpha < 1$ , the leaflet shape has a variable  
 35 radius of curvature having its axis of revolution in the x, y plane. This allows leaflets to be produced having a

shape to give the required properties which also fits within any given frame.

The valve radius,  $R_v$  as shown in Figure 3, and  $R_f$  are both in the range of 5 mm to 20 mm,  $g$  is in the range of 0 to 3 mm and  $\alpha$  is 0.5.

Leaflets of this shape open radially away from the centre of the frame out towards the wall of the artery with a very low pressure, typically below 1 mm Hg. This is important as if the valve 1 fails to open at low pressures, the blood will cease to circulate. The shape of the leaflets 2 also ensures that they rapidly close when the blood tries to flow in the reverse direction, therefore quickly preventing the blood from flowing in this direction.

Various sizes of frame 3 may be used depending upon the size of the artery. Due to the leaflets 2, a frame radius  $R_f$  of about 13.5 mm produces a valve having an effective orifice area of approximately 2.5 cm<sup>2</sup>. This typically allows approximately 4.5 litres per minute of blood to flow through, at which rate, the valve 1 has a closing regurgitant volume of less than 3 ml per stroke.

Although not shown, the valve may have only two or more than three flexible leaflets 2.

The precise size and shape of the leaflets 2 depends upon the particular size of vessel in which the valve 1 is to be used. In particular, the shape parameter  $\alpha$  of the leaflets 2, may be varied to produce a set of valves 1 of substantially the same size but different shapes to suit most applications. Alternatively, a set of heart valves 1 may be produced all of which have the same shape, but have different sizes for particular applications.

C L A I M S

1. A flexible leaflet heart valve for controlling the flow of blood in an artery comprising a substantially rigid frame (3), and a plurality of substantially identical flexible leaflets (2) mounted on the frame (3), characterised in that each flexible leaflet (2) is formed from part of a surface of revolution having its axis of revolution lying in a plane substantially orthogonal to the direction of blood flow through the valve (1), and a shape defined by the equation:

$$z^2 + y^2 = 2R_L (x - g) - \alpha (x - g)^2$$

- 15 where:  $g$  is the offset of the leaflet from the axis of the frame;  
 $R_L$  is the radius of curvature of the leaflet (2) at  $(g, 0, 0)$ ; and  
 $\alpha$  is the shape parameter and is greater than 0 and less than 1.

- 20 2. A flexible leaflet heart valve according to claim 1, in which  $\alpha$  is in the range 0.2 to 0.8.  
3. A flexible leaflet heart valve according to claim 1 or 2, in which  $\alpha$  is within the range 0.4 to 0.6.  
25 4. A flexible leaflet heart valve according to any of the preceding claims, in which  $\alpha$  is substantially 0.5.  
5. A flexible leaflet heart valve according to any of the preceding claims, in which  $x$  is in the range 0 to  $R_L$ ,  $y$ , when present, is in the range  $-R_L$  to  $+R_L$ , and  $z$  is in the range  $-1.8R_L$  to  $+0.2R_L$ .  
30 6. A flexible leaflet heart valve according to any of the preceding claims, in which  $R_f$  and  $R_L$  are both between 5 mm and 20 mm, and  $g$  is in the range 0 to 3 mm.  
7. A flexible leaflet heart valve according to any of the preceding claims including three flexible leaflets (2).  
35



8. A flexible leaflet heart valve according to any of the preceding claims, in which the rigid frame (3) has a substantially circular cross section.

5 9. A flexible leaflet heart valve according to any of the preceding claims, in which the leaflets are made from polyurethane and have a variable thickness in the range 0.15 mm to 0.2 mm.

Fig. 1.






Fig. 2.



2/2

Fig. 3.



## INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 93/00568

**I. CLASSIFICATION OF SUBJECT MATTER** (If several classification symbols apply, indicate all)<sup>6</sup>

According to International Patent Classification (IPC) or to both National Classification and IPC

Int.Cl. 5 A61F2/24

**II. FIELDS SEARCHED**Minimum Documentation Searched<sup>7</sup>

Classification System

Classification Symbols

Int.Cl. 5

A61F

Documentation Searched other than Minimum Documentation  
to the Extent that such Documents are Included in the Fields Searched<sup>8</sup>**III. DOCUMENTS CONSIDERED TO BE RELEVANT<sup>9</sup>**

Category <sup>10</sup>	Citation of Document, <sup>11</sup> with indication, where appropriate, of the relevant passages <sup>12</sup>	Relevant to Claim No. <sup>13</sup>
A	MEDICAL AND BIOLOGICAL ENGINEERING vol. 14, no. 2, March 1976, LONDON U.K. pages 122 - 129 D. N. GHISTA 'TOWARD AN OPTIMUM PROSTHETIC TRILEAFLET AORTIC-VALVE DESIGN' see page 123, column 2, line 4 - line 22; figures 3,4 see page 128, column 1, line 19 see page 128, column 2, line 5 - line 14 ---	1,7-9
A	US,A,3 320 972 (R.F. HIGH ET AL.) 23 May 1967 see column 2, line 61 - line 72; figures 1-5 ---	1,7-9
A	EP,A,0 114 025 (E. HENNIG) 25 July 1984 see claim 4; figures ---	1,7-9
	--- -/-	

<sup>10</sup> Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

**IV. CERTIFICATION**

Date of the Actual Completion of the International Search

02 JUNE 1993

Date of Mailing of this International Search Report

08.06.93

International Searching Authority

EUROPEAN PATENT OFFICE

Signature of Authorized Officer

WOLF C.

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claims No.
A	CA,A,1 232 407 (D. K. WALKER ET AL.) 9 February 1988 see claims 1,18,26; figures ---	1,8,9
A	GB,A,1 443 221 (MEDAC) 21 July 1976 see page 3, line 21 - line 53; figures ---	1,7
P,A	WO,A,9 212 690 (AUTOGENICS) 6 August 1992 see page 25, line 1 - page 27, line 14; figures 6F,6G -----	1,7,8

**ANNEX TO THE INTERNATIONAL SEARCH REPORT  
ON INTERNATIONAL PATENT APPLICATION NO.**

GB 9300568  
SA 71454

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

02/06/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A-3320972		None	
EP-A-0114025	25-07-84	DE-A- 3248560	05-07-84
		JP-C- 1673511	12-06-92
		JP-B- 3034942	24-05-91
		JP-A- 59120149	11-07-84
		US-A- 4575442	11-03-86
CA-A-1232407	09-02-88	US-A- 4759759	26-07-88
GB-A-1443221	21-07-76	None	
WO-A-9212690	06-08-92	US-A- 5163955	17-11-92

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**